

# WARREN

WET-20T-P/F

WET - 20 Ton equipment trailer



## WET-20T-P

Warren Equipment trailer - pintle pull with ramps lowered and raised (above)

Offered in both a pintle pull or drop deck 5th wheel design, the Warren Equipment Trailer offers a very functional design. This trailer can be used to transport your backhoe, track loader, front-end loader, other equipment or materials.



WET-20T-F 20 Ton Fifth wheel drop deck equipment trailer with tool storage box open

Warren Truck & Trailer, LLC - P.O. Box 425 - Talco, TX 75487 - (903) 379-3921 - Fax (903) 379-4400  
www.warrentruckandtrailer.com toll free (888) 734-4400

## WET - 20 Ton Equipment trailer - Pintle pull and Fifth wheel design

### Specifications: Pintle pull trailer - 10,395# empty weight

Overall Length	36'6" with W12 x 22#/ft. I-Beam main frame rails and 8" channel perimeter
Overall Width	100-1/2" with 1/4" fabricated and tapered 8" to 4" cross members and 36" deck height
Deck Dimensions	23 ft. long x 96" wide x 3/16" thick diamond plate floor sheet *
Dovetail	5 ft. 13 degree slope, with 2" x 2" x 1/4" angle climb cleats
Ramps	(2) 7 ft. long x 30" wide tubing frame with 2' x 2" x 1/4" angle cleats
Landing jack	Holland, 17" travel
Pintle hitch	Premier Drawbar, with 3 adjustable height settings rated at 15,000# @ tongue/100,000# gross
Safety chains	1/2" Grade 100 with hooks
Suspension	Hutch 9700 under mount 4 spring with H.D. high arch 3-leaf springs
Axles	(2) 5" round rated @ 22,500# each with 8-hole hub piloted outboard drums
ABS	WABCO anti lock air brakes on both axles (4S2M)
Tires	(8) General 215/75R17.5 rated at 36,320#
Electrical	USA Harness sealed wiring harness, sealed beam lights mounted in rubber grommets, 7 pin plug
Lashing	(10) D-Rings on perimeter channel
Color	Black as standard, other colors optional
GVWR	45,000# de-rated by tires

### Specifications: Fifth wheel trailer - 11,030# empty weight

Overall Length	37' 6" with W12 x 22#/ft. I-Beam main frame rails and 8" channel perimeter
Front deck	W14@22#/ft. I-Beam boxed uprights on 8' long deck with hinged lid over king pin storage area
Overall Width	100-1/2" with 1/4" fabricated and tapered 8" to 4" cross members and 36" deck height
Deck Dimensions	23 ft. long x 96" wide x 3/16" thick diamond plate floor sheet *
Dovetail	5 ft. 13 degree slope, with 2" x 2" x 1/4" angle climb cleats
Ramps	(2) 7 ft. long x 30" wide tubing frame with 2' x 2" x 1/4" angle cleats
Landing jack	Holland, 17" travel
Suspension	Hutch 9700 under mount 4 spring with H.D. high arch 3-leaf springs
Axles	(2) 5" round rated @ 22,500# each with 8-hole hub piloted outboard drums
ABS	WABCO anti lock air brakes on both axles (4S2M)
Tires	(8) General 215/75R17.5 rated at 36,320#
Electrical	USA Harness sealed wiring harness, sealed beam lights mounted in rubber grommets, 7 pin plug
Lashing	(10) D-Rings on perimeter channel
Color	Black as standard, other colors optional
GVWR	45,000# de-rated by tires

\* Deck plate available as one piece as an option



Let us quote you on modifying your existing trailer by adding our spring loaded ramps. The trailer shown to the left was modified to ease loading and unloading by adding our spring loaded ramps.



**We also build half round dump bodies and pup trailers. Give us a call.**

Warren Truck & Trailer, LLC - P.O. Box 425 - Talco, TX 75487 - (903) 379-3921 - Fax (903) 379-4400  
www.warrentruckandtrailer.com toll free (888) 734-4400