

WARREN

WQFT-SS

WQFT-SS Quarter Frame Steel Trash Dump Trailer



30 Foot Quarter Frame Trash Trailer with square front bulkhead, high side walls, optional AR-400 floor and rugged rear doors.



Dual rear doors with three, winch driven latches and extra heavy duty greaseable hinges. The doors have a fully boxed perimeter and are the strongest hinges and latches in the industry.



Trailers shown are in use by the City of Houston, TX.

Regardless of your haul, let us work with you to specify what you need for your job. We recommend our 1/4" thick AR-400 steel floor to prevent washboarding and increase life. When you don't know what might be loaded into a trailer on a trash haul, our many features pay off in the long run. The quarter frame design gives you lighter empty weight but keeps all the tires on the ground throughout the dump cycle. Custom material, side wall height and lengths are available. Available in 22-30 feet in length.



Proudly made in the U.S.A.

Warren Equipment, Inc. 2299 Hwy 92 East (P.O. Box 699) Plant City, FL 33563 (33564)
Phone (813) 752-5126; fax (813) 754-9545; Toll free (800) 752-9469

www.warrentrailers.com

www.dumptrucks.com

WQFT-SS Quarter Frame Steel Trash Trailer :Specifications

Specifications for our Quarter Frame Dump Trash Trailer with steel body and sub-frame:

Body:

- Width 102" outside; 93" inside
- Floor material 1/4" AR-400 steel
- Side material 10 gauge Hi-tensile steel
- Cross members 4" steel channel @ 5.4#/ foot
- Front bulkhead 3/16" Hi-tensile steel
- Tailgate 10 gauge "barn door" style with H.D. ratchet latches
- Paint-standard colors available



Running Gear:

- Tandem single point trunnion H-900 Hutch suspension
- 2S1M ABS system
- 16" I-beam sub-frame
- 5" round 25,000# rated axles
- 10 stud steel hubs and 8.25 x 22.5 hub piloted wheel
- 11R x 22.5 14 ply radial tires
- Drop stand landing gear (2-speed landing gear optional)
- Draft arms 3" x 5" x 1/4" wall A500 tubing
- Compression arms 4" x 4" 3/8" wall A500 tubing
- Full depth cross members
- Color coded air lines
- LED sealed wire harness in accordance with FMVSS 108
- Black Paint

Hydraulics:

- Front mount telescopic hydraulic cylinder (size depends on trailer length)
- Front mount quick disconnects

Options:

Many options such as tarp systems, liners, different material thicknesses, side and end heights, tires, wheels, and paint colors are available. Call and let us assist you in specifying the trailer you need.



Warren Equipment, Inc. 2299 Highway 92 East (P.O. Box 699) Plant City, FL 33563 (33564)
Phone (813) 752-5126; fax (813) 754-9545; Toll free (800) 752-9469

www.warrentrailers.com

www.dumptrucks.com