

WARREN

WRDT-AA

ALUMINUM BODY ALUMINUM FRAME DUMP TRAILER

Warren Aluminum Body Aluminum Frame type dump trailers are designed to maximize your legal payload.



MODEL WRDT-3030-AA

The Aluminum body and frame of the WRDT-AA model trailer is precision engineered, fabricated and welded to provide years of trouble free service.

AA model trailers can be specified with numerous optional features to meet your exact requirements; various tailgate designs, special lighting and paint are just a few of these items. Lengths are available in 22 to 38 ft. and can be equipped with multiple axles to achieve your weight and bridge goals.

The Warren aluminum dump trailer is engineered to insure maximum stability. The full depth frame cross-members help prevent torsional twisting when dumping and even when turning.



Proudly made in the U.S.A.



Warren Equipment, Inc. 2299 Hwy 92 East (P.O. Box 699) Plant City, FL 33563 (33564)
Phone (813) 752-5126; fax (813) 754-9545; Toll free (800) 752-9469

www.warrentrailers.com

www.dumptrucks.com

WRDT-AA SPECIFICATIONS



STANDARD BODY FEATURES:

- Length:** 22 feet and up
- Width:** 96" outside; 87" inside
- Floor Material:** 250" alloy, 5454-H34
- Cross Members:** 4" X 2.5" X .300 I-Beam extruded 6061 -T6 alloy w/3/8" aluminum wear pads
- Longitudinal:** 4" X 6" X 1/4" 6061 Stud longitudinal 72" long @ rear of trailer
- Side Material:** .160 alloy, 5454-H34 STD .190" & .250" optional
- Top Rail:** 4" boxed top, extruded 6061-T6 alloy
- Bottom Rail:** Extruded Aluminum 6061-T6 w/integral inner clean-out
- Vertical Uprights:** 8.5" extruded 6061-T6 alloy
- Front:** Full wrap around bulkhead and continuous welding
- Tailgate:** .190 plate, 5454-H34, extruded 6061-T6 braces,
3 1/2" air cylinder operated latch, steel bolt-on hinges
- Steps:** (3) outside rear panel—drivers side

STANDARD ALUMINUM CHASSIS FRAME:

- Suspension:** Hutchens, multi-leaf, auto-slacks, STD
- Axles:** 25,000 lb. capacity, 5" round
- Brakes:** 16 1/2" X 7" X3/4" -'S' cam air, quick-change non-asbestos
30/30 chambers 2S/1M ABS
- Hubs/Drums:** Outboard mount 10-stud, steel hub, piloted
- Wheels:** 8.25 X 24.5 or 22.5 steel disc
- Tires:** 11R-22.5 or 11R-24.5
- Lights:** LED FMVSS 108, 12 volt
- Landing Gear:** Holland drop stand
- Frame Rails:** Web 1/4" X length of trailer, 5083-H34, Top flange 1/2" X 4" 6061-T6, bottom flange,
3/4" X 4" X 10' 6061-T6 neck area, 1/2" X 4" 6061-T6 balance of trailer length
- Frame Construction:** Fabricated, full depth, 1/4" 5052-H32 cross-members, 3/8" suspension-5082-H32
- King Pin Plate:** 3/8" steel with 2" SAE kingpin

OPTIONAL EQUIPMENT:

- | | | | | |
|--------------|--------------------------|----------------------|---------------------|------------|
| Tarp Systems | 2-Speed Landing Gear | 6" Sloping Tailgate | Aluminum Wheels | Bed Liners |
| Wet Line Kit | Selection of Suspensions | Water Tight Tailgate | Side Swing Tailgate | |

Call and let us assist you in specifying the trailer you need.



MADE IN
THE U.S.A.



Warren Equipment, Inc. 2299 Highway 92 East (P.O. Box 699) Plant City, FL 33563 (33564)
Phone (813) 752-5126; fax (813) 754-9545; Toll free (800) 752-9469

www.warrentrailers.com

www.dumptrucks.com