

# WARREN

## WRDT-SS

### STEEL BODY STEEL FRAME DUMP TRAILER

Warren end dump trailers are designed to allow you to spec your trailer to match any haul you have.



#### MODEL WRDT-3030-SS

The steel body and frame of the WRDT-SS model trailer is precision engineered, fabricated and welded to provide years of trouble free service.

SS model trailers can be specified with numerous optional features to meet your exact requirements; hi-tensile steel, various tailgate designs, special lighting and paint are just a few of these items. Lengths are available in 22 to 38 ft. and can be equipped with multiple axles to achieve your weight and bridge law compliance goals.

The Warren steel dump trailer is engineered to insure maximum stability. The full depth frame cross-members help prevent torsional twisting when dumping and even when turning.



**WARREN**

Warren Equipment, Inc. 2299 Hwy 92 East (P.O. Box 699) Plant City, FL 33563 (33564)  
Phone (813) 752-5126; fax (813) 754-9545; Toll free (800) 752-9469

[www.warrentrailers.com](http://www.warrentrailers.com)

[www.dumptrucks.com](http://www.dumptrucks.com)



# WRDT-SS SPECIFICATIONS



Side swing closed



Side swing open



Electric aluminum arm tarp system shown w/STD wrap around bulkhead



Color coded air hose and grommet lined frame holes are standard

## STANDARD BODY FEATURES:

<b>Length:</b>	22' to 38'
<b>Capacity:</b>	20 to 50 cu. yards
<b>Width:</b>	96" outside; 87" inside
<b>Floor Material:</b>	3/16" High strength steel
<b>Cross Members:</b>	4" - 5.4#/ft. structural channels
<b>Longitudinal:</b>	6" - 12.5#/ft structural I-beam
<b>Side Material:</b>	10ga. High strength steel
<b>Top Rail:</b>	4" X 4" Structural wall square tubing
<b>Bottom Rail:</b>	4" X 4" Square tubing –structural wall square tubing w/ welded in dirt shedders
<b>Side Braces:</b>	Boxed 6" wide 10ga.
<b>Tailgate:</b>	3/16" 9-panel bracing, airlock
<b>Paint:</b>	Several standard colors / optional colors available

## STANDARD STEEL CHASSIS FRAME:

<b>Suspension:</b>	Hutchens, w/multi-leaf, spring
<b>Axles:</b>	25,000 lb. capacity, 5" round w/auto slack adjusters
<b>Brakes:</b>	16 1/2" X 7" - 'S' cam air, quick change non asbestos w/30/30 chambers
<b>Hubs/Drums:</b>	Outboard mount 10 stud, steel, hub piloted
<b>Wheels:</b>	8.25 X 22.5 or 24.5 steel disc
<b>Tires:</b>	11R-22.5 or 11R-24.5
<b>Lights:</b>	LED w/sealed wire harness in accordance w/FMVSS 108
<b>Landing Gear:</b>	Holland Drop legs
<b>Frame Rails:</b>	Web 3/16" X length of trailer, A-50 steel, top flange 1/2" X 4" X 10' steel Bottom flange 3/4" X 4" X 10' neck area, 1/2" X 4" balance of trailer length
<b>Frame :</b>	Fabricated. Full depth, 3/16" cross-members (1/4" over suspension)
<b>King Pin Plate:</b>	3/8" steel, 2" SAE kingpin
<b>ABS:</b>	2S/1M
<b>Mud flaps:</b>	1/2" H.D. rubber - plus 1/2" center chassis flap

## OPTIONAL EQUIPMENT:

Tarp Systems	2-Speed Landing Gear	Sloping Tailgate	Liners	Tarp rods	Vibrators
Wet Line Kit	Selection of Suspensions	AR-400 Steel floor	Aux. engine driven hyd. pump		
Special lights	Aluminum Wheels	Extremely H.D. trash trailer higher cube specifications			
Remote bleeder & grease connections for easy cylinder & upper hoist maintenance					
Upper hoist (cylinder) pivot					



MADE IN  
THE U.S.A.



Warren Equipment, Inc. 2299 Highway 92 East (P.O. Box 699) Plant City, FL 33563 (33564)  
Phone (813) 752-5126; fax (813) 754-9545; Toll free (800) 752-9469

[www.warrentrailers.com](http://www.warrentrailers.com)

[www.dumptrucks.com](http://www.dumptrucks.com)